

A word from the author:


Rivet is a open source decoder written in Java which decodes various HF data modes that have either been forgotten by the better known decoder programs or which can only be decoded by expensive programs that are beyond the reach of the average hobbyist. The program doesn't need any other hardware to operate all it requires is a sound card with an audio feed from HF receiver.

Those of you who have used decoder programs for HF data modes before will find Rivet a little different. Firstly Rivet doesn't need you to precisely tune your receiver to signal for it to be decoded. Instead Rivet takes advantage of a modern PCs processing power and adjusts itself to the incoming signal. This means you don't waste vital minutes messing around with a tuning indicator when you want to see what is being transmitted. The downside is that Rivet does need to run on a fairly powerful PC with at least 2 cores. Secondly Rivet is designed not only to accept a direct sound input from a sound card but it can also decode data from a .WAV file (which must be mono and have a sample rate of 8 KHz). So you can record a transmission while you are searching through the HF spectrum and record it later. If you click [here](#) you will find several recordings you can use to test the program.

Lastly Rivet is a free and open source program something which is very unusual for a HF data mode decoder. To make it better I need your input so if you find any bugs or have any feature suggestions please email me. If you are a programmer then use Github to fork Rivet and add some new features yourself then if I like them I will add them to the program.

Ian Wraith

Menus



Main

- **Copy All to the Clipboard**

The entire contents of the screen display are copied into your clipboard. Useful if you wish to include a section of a decode from Rivet in an email or word processor document.
- **Load a WAV File**

Rivet not only decodes audio directly from your radio but can also decode data contained in WAV files which were recorded previously. Note that Rivet can only decode WAV files which were recorded in mono mode and at certain sample rates (usually 8000 Hz).
- **Reset Decoding State**

If this menu item is selected then Rivet resets to the default settings for the particular mode you have selected. So if Rivet has set its levels and symbol timing on a signal and this option is selected then Rivet will reset and try to reacquire levels and symbol timing.
- **Save the Current Settings**

If you click on this all of the settings you have selected (Mode etc) will be saved in a file called "rivet_settings.xml". From then onwards when you restart Rivet the program will load these settings and use them as its default. To change this select the settings you would like to be your new default and click on this item again.
- **Save to File**

When this option is enabled all traffic that is decoded by Rivet will also be saved to an ASCII text file. When you select this option a dialog box will appear requesting you give a name and a location for this file.
- **Save Bit Stream to File**

When you enable this option the program will ask you to select a file name and folder for the file. Afterwards the raw binary output from the program will be saved in that file (which has a .bsf prefix). It is then possible for you to analyse the data in this file for the purpose of reverse engineering a mode. Please note that this option only currently works when decoding selected modes.
- **Soundcard Input**

When this is enabled Rivet will accept and attempt to decode audio from the audio source selected by your PC's mixer. I would recommend that you use your PC's Line Input source for this.
- **Exit**

Use this to shut down the program.

Modes

Use this menu to select the mode you wish to decode.

- CCIR493-4 : A HF selective calling mode
- CIS36-50 (50 baud only currently) : Used by the Russian Navy.
- CROWD36 : Used for Russian diplomatic and intelligence messages
- FSK200/500 : Used for Russian diplomatic and intelligence messages
- FSK200/1000 : Used for Russian diplomatic and intelligence messages
- FSK (raw) : For advanced users to investigate unknown FSK modes
- GW FSK (100 baud) : A commercial ship to shore data system.
- XPA (10 and 20 baud) : Believed used for Russian intelligence messages.
- XPA2 : Believed used for Russian intelligence messages.

Options

- **Baudot & FSK options**

Here you can enter several options for Baudot & FSK modes

- **Debug Mode**

When this mode is enabled Rivet will display debugging and diagnostic information about the signal it is decoding. Unless you are a developer I wouldn't recommend you enable this option.

- **Invert**

When enabled the data received by Rivet will be inverted. So for example if a FSK (Frequency Shift Keying) mode is being received and the high tone normally represents a 1 and a low tone a 0 , if this option is enabled then the high tone will represent a 0 and the low tone a 1. In some modes (e.g CCIR493-4) Rivet will automatically decide if Invert needs to be enabled or disabled and will change it accordingly.

- **Set the CROWD36 High Sync Tone**

This option is used when you are in CROWD36 mode to tell Rivet the tone number of the high sync tone being used by the CROWD36 station you are monitoring.

- **CIS36-50 options**

Here you can enter several options for the CIS36-50 mode.

Triggers

The author explains this function here:

<http://decodermusings.blogspot.nl/2013/02/an-introduction-to-rivet-trigger-feature.html>

View

- **View GW Free Channel Markers.**

If you are decoding the shore side of GW 100 baud FSK channel you will see a free channel marker decoded every few seconds. This will soon fill Rivets display and may become annoying. If you disable this option the program will ignore free channel markers and you will only see other traffic.

- **Display possible bad data**
- **Display UTC time**
- **Clear display**

Help

- **About Rivet**
Informs you of the version of Rivet you are using and some information about the author.
- **Enigma2000**
This option takes you to a web page giving information about the Enigma2000 group.
- **UDXF**
This option takes you to the UDXF website.
- **Follow Rivet Progress on Twitter**
This takes you to Rivets authors Twitter page. Follow me to find out the latest news on Rivet.
- **Help**
This takes you to the Rivet help pages.
- **Sound Sample Files**
Takes you to a web page where you can download sample sound files to decode using Rivet.
- **More Information on the Modes Decoded By Rivet**
 - CCIR493-4
 - CIS36-50
 - CROWD36
 - FSK200/500
 - FSK200/1000
 - GW 100 Baud FSK
 - XPA
 - XPA2

CCIR493-4

- This mode is used for individual and group selective calling on the HF bands. The data consists of short bursts of 100 baud FSK (Frequency Shift Keying) with a shift of 170 Hz. Rivet decodes this data and displays it so it looks like this ..
12:53:51 CCIR493-4 Individual Selective Call Station 2522 Calling 2519 (Routine)
- CCIR493-4 data can either be decoded live from a HF radio connected to your soundcards line in input or from a prerecorded WAV file. This WAV file however must be recorded in mono mode with a 8000 Hz sample rate.
- To decode this mode tune your radio to the frequency where you know CCIR493-4 is used with the receiver set to either USB or LSB modes. Rivet will wait for the brief CCIR493-4 synchronisation sequence and adapt itself from that then decide if the signal needs to be inverted or non-inverted automatically.

CIS36 50

- This mode can be found all over the HF bands. It is believed to be a Russian Naval mode which transmits FSK (Frequency Shift Keying) at a data rate of 50 baud with a 200 Hz shift and is sometimes known as BEE. Some stations transmitting this mode transmit constantly sending idles between messages while others only transmit when a message is due at fixed intervals. All the CIS36-50 transmissions decoded so far have been encrypted and look like this ..

FSK 200/1000

- This mode is believed to be used by the Russian intelligence services. Data is transmitted using FSK (Frequency Shift Keying) at a speed of 200 baud with a 1000 Hz shift.

FSK 200/500

- This mode is believed to be used by one of the Russian intelligence services. It transmits data using FSK (Frequency Shift Keying) modulation with the ITA-2 alphabet (with 1.5 stop bits) at a speed of 200 baud with a shift of 500 Hz.
- Rivet can decode FSK200/500 messages directly from a radio in USB mode connected to a soundcards line input or from a WAV file that is mono and with a sample rate of 8000 Hz. The program calibrates itself by looking at the incoming audio and then starts to decode and display the message on the screen. Once a message is decoding do not retune your radio until the message is complete.
- When there is no message to send in a schedule the line ..
00000+++++++162)5761
will be sent continuously for seven minutes. When there is a message offline encryption is sent which starts like this ..
00000+++++++188=8331
52281013891141343 =8432
92874574809254333 =8573
814347960943078155=8794
- The number to the left of the = sign appears to be the encrypted traffic and consists of 17 or 18 digits. The number to the right is interesting also though. The last digits of this is the line number which you can see incrementing. The messages ends like this ..
28870268039372698 =81275
423345851935701126=86276
88837514787689596 =81277
26158186121423068)57678
- Certain 3 digit codes appear to have special meanings. The ones we have come across so far are ..
162 Start of a null message
188 Start of a message
576 End of message or null

GWK 100Bd FSK

This mode is one of several used by a commercial communications company to contact ships at sea and to send data to them. The mode is defunct now.

XPA

- This is a Russian mode believed to be used by at least one of the Russian intelligence services. It transmits data at either 10 baud (most commonly) or 20 baud using 17 tone MFSK (Multi Frequency Shift Keying).
- Rivet can decode XPA live from a radio (using your soundcards line in input) or from . WAV file recording which is mono and with a sample rate of 11024 KHz or 8000 KHz. The program begins its operation by hunting for the XPA synchronization sequence by looking for four tones (tone #1 , tone #2 , tone #3 and tone #4) it then checks that tones #1 and #3 are the same and that tones #2 and #4 are the same, finally it then checks that there is 760 Hz difference between tones #1 and #2. At that point the program calibrates its timing and the frequency offset of the transmission. Once Rivet has done this do NOT change the tuning of your radio.
- A decoded XPA message looks like this ..

```
13:13:58 XPA Start Tones Found (correcting by 36 Hz)
13:14:03 High sync tone found
13:14:03 Symbol timing found
Block Sync
4444444444
Block Sync
101 101 101 1 101 101 101 1 101 101 101 1
4444444444
Block Sync
6
Message Start
00857 00097 93286 71395 40333 00714 17852 48857 77718 50780 37834 00215 21772 68734 13603
85646 14094 40723 82696 11038 43675 98847 50732 30954 17592 54577 90765 62197 87165 86007
68736 35714 24007 86209 96271 89625 35714 19269 81590 60485 02469 82980 59119 82461 77523
86731 22993 12521 52548 97909 55084 10648 78945 97123 16673 97138 83388 34822 60415 93306
50071 38438 27154 80657
Block Sync
82050 37623 04296 14200 72261 30215 93943 34679 68188 53956 79136 08478 30933 72586 38826
06910 55823 18377 89051 96813 05847 91457 30993 17025 36671 20034 7380 08659 34217 05873
30813 11871 61634 20351 39596 7426
13:14:03 XPA Decode Complete
```

XPA2

- XPA2 is a Russian mode believed to be used by at least one of the Russian intelligence services. It transmits data at the unusual rate of 7.8 baud using 14 tone MFSK (Multi Frequency Shift Keying).
- Rivet can decode XPA2 live from a radio (using your soundcards line in input) or from . WAV file recording which is mono and with a sample rate of 11024 KHz or 8000 KHz. The program begins its operation by hunting for the XPA synchronization sequence by looking for four tones (tone #1 , tone #2 , tone #3 and tone #4) it then checks that tones #1 and #3 are the same and that tones #2 and #4 are the same, finally it then checks that there is 234 Hz difference between tones #1 and #2. At that point the program calibrates its timing and the frequency offset of the transmission. Once Rivet has done this do NOT alter the tuning of your radio.
- A decoded XPA2 message looks like this ..

13:49:52 XPA2 Start Tones Found (correcting by -1 Hz)
13:50:29 Symbol timing found
02435 00146 98804 73855 93507 32951 32279 89275 85524 53888 95942 92198 90557 04769 54888
20926 94351 53313 31155 63773 55936 08424 26549 01634 43739 83041 11786 65426 09526 69705
28433 53534 59595 88768 38470 64642 94623 09572 01779 46864 48326 44457 80870 13778 58331
70218 02211 33066 78858 82209 34788 24458 27877 14600 16550 66300 53399 36220 66529 80022
84492 18763 77921 74517 06590 40668 78325 11660 78097 35235 66565 05193 08038 23858 02838
96632 12334 57529 31361 97524 06251 73501 56953 86309 65431 43780 17915 56730 12549 07132
34694 22306 01444 55806 17712 69823 33014 07770 37248 06682 33638 30834 75725 02321 58679
91992 44526 72421 05908 33798 91084 28280 23088 32018 74665 75705 58256 00465 27697 04388
37650 93575 06837 46454 84140 47744 88681 77535 49948 27777 43165 11011 80486 68013 91912
97794 76189 68125 99885 31533
13:50:30 XPA2 Decode Complete

FAQ

1. Why doesn't Rivet have a .exe file ? How do I install and run it ?

Rivet is written in a programming language called Java which allows it to run on computers using a variety of operating systems which include MS Windows , Apple OS X and Linux. Instead of having a .exe file it has a .jar file. To run the program you must first install Oracle Java which is free can be downloaded from [here](#). To install Rivet go to the Github download page and click on the link that says "rivet_bxx.jar" where xx is the build number. Save that file into a folder on your PC. Then to run it go to that folder and double click on that .jar file , within a few seconds Rivet should run. A common problem is that Rivet appears to a folder containing lots of files. The usual cause of this is that an unzip type program has decided that it "owns" .jar files rather than Oracle Java.

2. How do I know my radio is tuned correctly ? and why doesn't Rivet have a tuning aid ?

That is where Rivet is different ! In the past decoders require that you tune your radio precisely to the audio frequencies it expects the data to be at. Rivet takes advantage of a modern computers amazing processing power to look at an incoming signal and then it adapts itself to the signal so no tuning aid is needed. This means you can also decode data you recorded in .WAV sound files previously.

It is important to remember that Rivet adapts itself to a signal in different ways depending on the mode being monitored. With FSK200/500 , FSK200/1000 and GW 100 Baud FSK the program simply looks for the two frequencies separated by the correct bandwidth. With the MFSK modes things are more complex. So with XPA and XPA2 Rivet needs to see the modes start of message sequence to calibrate itself.

3. Why doesn't Rivet decode this mode ?

I probably just haven't got around to adding it ! Working on Rivet is a hobby of mine and sadly I never have as much time as I would like to work on it. If you know of a mode you would like Rivet to decode please contact me and tell me about it.

4. How could I help improve Rivet ?

I am looking for three kinds of people ..

5. If you are a Java programmer and are interested in helping please use Github to fork this project and feel free to add any modes or make any changes you want , it is a fully Open Source project. However I would be very grateful if you could send me your changes so I can include them in Rivet and everyone can take advantage of them.

I will admit that Rivets documentation needs a lot of work to improve it. If you want to help with that please get in touch.

6. Rivet doesn't start. If you doubleclick on a jar file, and your Java application does not start, your .jar association has been hijacked. You can fix the problem with Jarfix.

<http://johann.loefflmann.net/en/software/jarfix/index.html>

7. More Java problems. Error: "Could not create the java virtual machine"

If Jarfix doesn't help, try this:

Go to the Windows config screen; then System; then Advanced

Go to Environmental Variables

Add a new variable:

Variable name: _JAVA_OPTIONS

Variable value: -Xmx512M

This specifies the maximum size, in bytes, of the memory allocation pool.